

This assignment has several questions that warrant proofs. Try to emulate the proof style that we have used in class and the proof style that appears in the text. That is, make sure your reasoning flows logically from one statement to another. You should edit your proofs to make sure they read well. Abstraction is crucial. That is, identify and isolate common ideas. Write clearly and concisely or use \LaTeX to typeset your solutions.

On homework assignments throughout the semester, hints will be provided in QR codes in the margin, numbered by their corresponding question. Some questions may have multiple hints; generally the hints are in order of hintiness. If you do not have a device capable of reading QR codes, you can find the hints in the `.tex` source for this document, linked from the course webpage.

Start early. Ask for help if you need it. Have fun!

Question 1. *Decide whether you think the following statements are true or false. If a statement is true, give a short explanation/proof. If it's false, give a counterexample.*

- (a) *For every instance of the Stable Matching Problem, there is at least one stable matching containing a pair (p, a) such that p is ranked first on the preference list of a and a is ranked first on the preference list of p .*
- (b) *Consider an instance of the Stable Matching Problem in which there exists a proposer p and an acceptor a such that p is ranked first on the preference list of a and a is ranked first on the preference list of p . Then the pair (p, a) belongs to every possible stable matching for this instance.*

Question 2. *Consider the following problem, called the Stable Roommate Problem. There are $2n$ people, each of whom ranks the other $2n - 1$ people in order of cohabitation preference. For example, Alice, Bob, Carlos, and Don might have the following rankings:*

Name	Preference		
Alice	Bob	Carlos	Don
Bob	Alice	Carlos	Don
Carlos	Don	Alice	Bob
Don	Carlos	Alice	Bob

The goal is to find a stable matching (i.e., n pairs of roommates such that no two people prefer each other to their current roommate). We saw in class that a stable matching always exists for instances of the stable matching problem. Do stable matchings always exist for the stable roommate problem? If so, provide a proof. If not, give a counterexample.

Question 3 (Algorithms in the wild). *The National Residency Matching Program (NRMP) matches medical students with residency programs. Here is what the NRMP says on their website:*



2

The NRMP Main Match provides an impartial venue for matching applicants' preferences for residency positions with program directors' preferences for applicants. Each year approximately 16,000 U.S. allopathic medical school seniors and 15,000 graduates of osteopathic, Canadian or foreign medical schools compete for approximately 24,000 residency positions.

In this matching problem, there are n students and m hospitals. Each hospital h_i has p_i available positions. Each student ranks the m hospitals and each hospital ranks the n students. Since there are more students than total positions available, we assume that $n > \sum_{i=1}^m p_i$. Thus, some students are never matched. As a result, we need a slightly expanded version of stability. As before, the matching is unstable if

- *s is assigned to h and s' is assigned to h' but s prefers h' to h and h' prefers s to s' .*

But it is also unstable if

- *s is assigned to h and s' is not assigned to a hospital but h prefers s' to s .*

Give an algorithm to find a stable matching of students to hospitals where every hospital position is filled with a student. Prove that your algorithm is correct.

3



Question 4. *Implement your algorithm from Question 3 in a programming language of your choice. Your program should take two files `sranks` and `hranks` as input. The file `sranks` is a ranking of hospitals for each student. The format of the file is*

```
student_name1, hos_rank1, hos_rank2, ..., hos_rankm
student_name2, hos_rank1, hos_rank2, ..., hos_rankm
.
.
```

The file `hranks` is a ranking of students for each hospital. The format of the file is

```
hospital_name1, numslots, stu_rank1, stu_rank2, ..., stu_rankn
hospital_name2, numslots, stu_rank1, stu_rank2, ..., stu_rankn
.
.
```

where `numslots` is the number of available slots for that hospital. The output should be a stable matching of students to hospitals. The format of the output should be

```
hospital1, student1, student2, ...
hospital2, student1, student2, ...
.
.
```

where each hospital is assigned the appropriate number of students. Run your program on the `srank`s and `hrank`s files linked on the course website. If you need help choosing a programming language or figuring out how to read and parse the input files, please come talk to me!

Submit a **printout of your program** along with the rest of this assignment. Submit the properly formatted output file **electronically via Moodle** (so that I can run automated tests to ensure your generated matching is stable).

Question 5. On a scale of 1 to 10, with 1 being “my pet goldfish could do it in its sleep” and 10 being “who do you think I am, Einstein?”, how difficult was this assignment? How many hours would you estimate that you spent on it?